


## Standard Recovery Diodes (Hockey PUK Version), 1070A

### FEATURES

- Wide current range
- High voltage ratings up to 6000V
- High surge current capabilities
- Diffused junction
- Hockey PUK version
- Case style DO-200AB(B-PUK), Nell's C-type Capsule
- Lead (Pb)-free



DO-200AB(B-PUK)  
(Nell's C-type capsule)

### TYPICAL APPLICATIONS

- Converters
- Power supplies
- Machine tool controls
- High power drives
- Medium traction applications

PRODUCT SUMMARY	
I <sub>F(AV)</sub>	1070A

MAJOR RATINGS AND CHARACTERISTICS				
PARAMETER	TEST CONDITIONS	D1070C		UNIT
		36 to 45	50 to 60	
I <sub>F(AV)</sub>		1070	1030	A
	T <sub>hs</sub>	55	55	°C
I <sub>F(RMS)</sub>		2040	1910	A
	T <sub>hs</sub>	25	25	°C
I <sub>FSM</sub>	50 HZ	12000	7200	A
	60 HZ	12560	7530	
I <sup>2</sup> t	50 HZ	720	259	kA <sup>2</sup> s
	60 HZ	655	235	
V <sub>RRM</sub>		3600 to 4500	5000 to 6000	V
T <sub>J</sub>	Typical	-40 to 150		°C

### ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS				
TYPE NUMBER	VOLTAGE CODE	V <sub>RRM</sub> , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	V <sub>RSM</sub> , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	V <sub>RRM</sub> , MAXIMUM AT T <sub>J</sub> = T <sub>J</sub> MAXIMUM mA
D1070C	36	3600	3700	50
	40	4000	4100	
	45	4500	4600	
	50	5000	5100	
	54	5400	5500	
	56	5600	5700	
	58	5800	5900	
	60	6000	6100	







FORWARD CONDUCTION		PARAMETER	SYMBOL	TEST CONDITIONS	D1070C		UNIT	
36 to 45	50 to 60				36 to 45	50 to 60		
Maximum average forward current at heatsink temperature		$I_{F(AV)}$		180° conduction, half sine wave Double side (single side) cooled	1070 (550)	1030 (520)	A	
					55 (85)	55 (85)	°C	
Maximum RMS forward current		$I_{F(RMS)}$		25°C heatsink temperature double side cooled	2040	1910	A	
Maximum peak, one cycle non-repetitive surge current		$I_{FSM}$	t = 10ms	No voltage reapplied  100% $V_{RRM}$ reapplied	12000	7200	A	
			t = 8.3ms		12560	7530		
			t = 10ms		10080	6050		
			t = 8.3ms		10550	6325		
Maximum $I^2t$ for fusing		$I^2t$	t = 10ms	No voltage reapplied  100% $V_{RRM}$ reapplied	720	259	$kA^2s$	
			t = 8.3ms		655	235		
			t = 10ms		508	183		
			t = 8.3ms		462	166		
Maximum $I^2\sqrt{t}$ for fusing		$I^2\sqrt{t}$	t = 0.1 to 10 ms, no voltage reapplied		7200	2592	$kA^2\sqrt{s}$	
Low level value of threshold voltage		$V_{F(TO)1}$	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ $T_J = T_J$ maximum		0.9	1.10	V	
High level value of threshold voltage		$V_{F(TO)2}$	$(I > \pi \times I_{F(AV)}), T_J = T_J$ maximum		1.2	1.35		
Low level value of forward slope resistance		$r_{t1}$	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ $T_J = T_J$ maximum		0.45	0.58		
High level value of forward slope resistance		$r_{t2}$	$(I > \pi \times I_{F(AV)}), T_J = T_J$ maximum		0.34	0.46	$m\Omega$	
Maximum forward voltage drop		$V_{FM}$	$I_{pk} = 2000A, T_J = T_J$ maximum, $t_p = 10$ ms sinusoidal wave		1.95	2.55	V	

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER		SYMBOL	TEST CONDITIONS		VALUES	UNIT
Maximum junction operating temperature range		$T_J$			-40 to 150	°C
Maximum storage temperature range		$T_{stg}$			-55 to 200	
Maximum thermal resistance, junction to heatsink		$R_{thJ-hs}$	DC operation single side cooled		0.073	K/W
			DC operation double side cooled		0.031	
Mounting force, ±10%					14700 (1500)	N (kg)
Approximate weight					250	g
Case style			DO-200AB (B-PUK), Nell's C-type Capsule			


$\triangle R_{thJc}$ CONDUCTION						
CONDUCTION ANGEL	SINUSOIDAL CONDUCTION		RECTANGULAR CONDUCTION		TEST CONDUCTIONS	UNITS
	SINGLE SIDE	DOUBLE SIDE	SINGLE SIDE	DOUBLE SIDE		
180°	0.009	0.009	0.006	0.006	$T_J = T_J$ maximum	K/W
120°	0.011	0.011	0.011	0.011		
90°	0.014	0.014	0.015	0.015		
60°	0.020	0.020	0.021	0.021		
30°	0.036	0.036	0.036	0.036		

**Note**


- The table above shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC

**Fig.1 Current ratings characteristics**

**Fig.2 Current ratings characteristics**

**Fig.3 Current ratings characteristics**

**Fig.4 Current ratings characteristics**

**Fig.5 Forward power loss characteristics**

**Fig.6 Forward power loss characteristics**



**Fig.7 Maximum non-repetitive surge current single and double side cooled**




**Fig.9 Current ratings characteristics**




**Fig.11 Current ratings characteristics**




**Fig.8 Maximum non-repetitive surge current single and double side cooled**










**Fig.10 Current ratings characteristics**



**Fig.12 Current ratings characteristics**



**Fig.13 Forward power loss characteristics**

**Fig.14 Forward power loss characteristics**

**Fig.15 Maximum non-repetitive surge current single and double side cooled**

**Fig.16 Maximum non-repetitive surge current single and double side cooled**

**Fig.17 Forward voltage drop characteristics**

**Fig.18 Forward voltage drop characteristics**



**Fig.19 Thermal Impedance  $R_{thJ-hs}$  characteristics**

**ORDERING INFORMATION TABLE**

Device code	D	1070	C	40
	(1)	(2)	(3)	(4)


- [1] - "D" for standard recovery diode
- [2] - Maximum average forward current, "1070" for 1070A
- [3] - Case style : "C" for Nell's C-type Capsule, DO-200AB (B-PUK)
- [4] - Voltage code, code x 100 =  $V_{RRM}$

**DO-220AB (B-PUK), Nell's C-type Capsule**

$\varnothing 3.5$  (0.14) NOM. x  
1.8 (0.07) deep MIN. both ends



0.8(0.03) MIN.  
both ends              Ø34 (1.34) MAX.  
                        2 places



K  
A

All dimensions in millimeters (inches)